



26" / 650 mm Super Dragon™ Dredge

| | 26" English | 650 mm Metric |
|--|----------------|------------------|
|--|----------------|------------------|

| | | | |
|---|---------------------------------------|----------------|-----------------|
| GENERAL | Suction Pipe x Discharge Pipe | 26" x 26" | 650 mm x 650 mm |
| | Dredging Depth, Maximum | 59' | 18 m |
| | Length, Overall (with Ladder Raised) | 187' | 57 m |
| | Length, Hull | 105' | 35.2 m |
| | Length, Hull (with Spud Carriage) | 151' | 46 m |
| | Width, Hull (including Side Pontoons) | 47'-7" | 14.5 m |
| | Depth Hull | 9' | 2.75 m |
| | Number of Pontoons (tanks) | 3 | 3 |
| | Shell Plate Thickness | 5/16" | 8 mm |
| | Dry Weight | 1,350,000 lbs | 612,250 kg |
| | Hull Draft (not Including Spuds) | 5'-7" | 1.7 m |
| | Fuel Capacity | 12,000 gallons | 45,500 liters |
| | Swing Width @ Min. Dredging Depth | 238' | 72 m |
| | Swing Width @ Max. Dredging Depth | 198' | 60 m |
| ENGINES | Main Engine (Caterpillar) | Marine 3516C | |
| | Power | 2,447 HP | 1,825 kW |
| | Rating | Tier 3 | |
| | Cooling | Box Cooler | |
| | Auxiliary Engine | Marine C-32 | |
| | Power | 1,410 HP | 969 kW |
| | Rating | Tier 3 | |
| | Cooling | Box Cooler | |
| TOTAL INSTALLED POWER | Including Standard Genset | 3,808 HP | 2,842 |
| | Power at Cutter Shaft | 600 HP | 448 kW |
| | Cutter Speed | 0-36 RPM | |
| CUTTER DRIVE | Cutter Diameter | 85" | 2,159 mm |
| | Cutting Force | 12,500 lbs | 5,670 kg |
| SPUDS AND SPUD CARRIAGE | Diameter | 31'-6" | 800 m |
| | Length | 78'-4" | 23.75 m |
| | Spud and Carriage (Travel) | 13'-2" | 4 m |
| | Spud Carriage (Pushing Force) | 35,000 lbs | 17,237 |
| Preliminary Specifications are Subject to Change Without Notice | | | |

Rev. 7/29/19